


Medicine Cabinet Specification Sheet

INSTALLER FRIENDLY

All holes are pre-drilled and threaded. Doors are packaged separately for safe handling and ease of cabinet installation, and install in minutes with snap on Blum hinges.

5/16" ADJUSTABLE SHELVES

5/16" glass shelves with polished front and side edges



MIRROR INSIDE AND OUT

Manufactured according to national mirror specifications; front door - 4mm, inside door - 3mm, inside box - 3mm.



ANODIZED ALUMINUM BODY

Solid anodized aluminum extrusions, .090 thick wall. Available in painted black, painted white, or clear anodize aluminum.



DOORS

Aluminum extrusions, soft close bumper

WIDE FINGER PULLS

Wide finger pulls for easy opening

BLUM HINGES

Effortless snap on adjustable Blum hinges open to 170 degrees, or use limit clips (included) when a 130 degree opening is required.



| Model | Actual Cabinet Width | Actual Cabinet Height | Actual Door Width | Actual Door Height* |
|-------|----------------------|-----------------------|-------------------|---------------------|
| 1524 | 15" | 24" | 14-7/8" | 24" |
| 1530 | 15" | 30" | 14-7/8" | 30" |
| 1540 | 15" | 40" | 14-7/8" | 40" |
| 1930 | 19" | 30" | 18-7/8" | 30" |
| 1940 | 19" | 40" | 18-7/8" | 40" |
| 2330 | 23" | 30" | 22-7/8" | 30" |
| 2340 | 23" | 40" | 22-7/8" | 40" |

* Arched doors - add 4" to actual door height at center of arch

| Cabinet Depth | Actual Unit Depth | Cabinet Only Depth | Recesses Into Wall |
|---------------|-------------------|--------------------|--------------------|
| 4" | 4-3/4" | 3-7/8" | 3-3/4" |
| 6" | 6-3/4" | 5-7/8" | 5-3/4" |

CUSTOM SIZES AVAILABLE

ELECTRIC OPTION

Use a 120 VAC 20 AMP GFI circuit
 Up to 4 cabinets can be wired to the circuit
 Includes 2 outlets
 Contains a 50 watt door heater
 The door included with this option is equipped with a disconnect cord. The door hinge orientation (left or right) must be designated during the ordering process.



Inside View



Back View

Rough Opening Calculation:

Rough Opening Width = cabinet(s) width less 3/4"
 Rough Opening Height = cabinet height less 5/8"
 At least 1" clearance above any obstructions is recommended